



eco OPTIDRIVE™

AC Variable Speed Drive

PUMP CONTROL

Energy efficient pumping with **OPTIFLOW™**




 **BACnet®**
MS/TP
built-in as standard

**Low Harmonic
Design**
EN 61000-3-12
Compliant

0.75kW – 250kW / 1HP – 350HP
200 – 600V Single & 3 Phase Input





OPTIFLOW™
Multiple Pump Control

BACnet®
 MS/TP
 built-in as standard

Internal EMC Filter



Energy Efficient Pump Control

- AC Induction (IM) Motors
- AC Permanent Magnet (PM) Motors
- Brushless DC (BLDC) Motors
- Synchronous Reluctance (SynRM) Motors


Energy Efficient Pumping

When a pump or pump set is selected, it must be suitable for operation during periods of maximum flow demand. In many applications, this maximum flow level may be rarely required, and as such the pump may operate for long periods at less than maximum flow capacity. By varying the speed of the pump to match the actual flow demand, significant energy savings are possible.

Optidrive Eco Pump has been designed to maximise the energy savings potential in pumping applications, whilst also providing significant additional benefits

in reduced installation costs, maintenance costs and downtime. Throughout all this, Invertek's "Ease of Use" philosophy ensures that advanced features are simple to commission, without requiring extensive, in depth knowledge of a huge number of parameters. Optidrive Eco Pump has a simple menu structure, and provides just the right amount of parameters to allow flexibility without over complication.

Overall, this provides the perfect balance of Easy to Install, Easy to operate, Advanced Pump Control.



Energy Savings Calculator

Estimate your potential energy savings, CO₂ emissions and financial savings
www.invertekdrives.com/calculator





Save Energy

Eco vector operation, based on Invertek's advanced motor control provides the most energy efficient operation of the pump, continually optimising the output to match the required flow with minimum energy consumption.

Advanced sleep & wake functions provide maximum energy savings by switching off the pump when not required

Save Money

OPTIFLOW™ technology allows simple operation of multiple pump sets without the need for a PLC

Pump blockage detection and cleaning dramatically reduces pump maintenance requirements

Built in PLC function allows bespoke customised applications to be programmed directly in the drive

Save Time

Simple parameter set allows fast commissioning of pump control systems

Pump operating curve detection automatically detects and monitors normal pump behaviour and is able to react when pumping conditions change

Customisable OLED display provides excellent visibility of drive status and operation in all conditions

Key Features



ECO Vector Motor Control



Standard Induction Motors



Permanent Magnet AC Motors

Brushless DC Motors

Synchronous Reluctance Motors

Energy Optimised Design



Internal EMC Filter



Low Noise Operation



Maximum Pumping Efficiency

Unique Eco Vector Sensorless Control


Optidrive Eco Pump uses advanced motor control technology, designed to provide the most energy efficient motor control possible. Operation with standard IM Motors, Permanent Magnet or Synchronous Reluctance motors is possible, all without requiring any feedback device or optional modules – simply change parameters to suit the connected motor, autotune and operate!

Eco Vector continuously adjusts in real time to provide the most efficient operating conditions for the load, typically reducing energy consumption by 2 – 3% compared to standard AC drives – providing similar long term costs savings to selecting a higher efficiency motor.

Energy Optimised Design

Optidrive Eco Pump up to frame size 5 are designed with film capacitors, replacing the traditional electrolytic capacitors used in the DC link. Film capacitors have lower losses, and also remove the need for AC, DC or swinging chokes, improving overall drive efficiency. Efficiency is improved by up to 4% compared to standard AC drives, whilst also reducing supply current total harmonic distortion (iTHD), improving the Real Power Factor and reducing total input current, leading to cost savings on installation through reduced cable and fuse ratings and smaller supply transformer rating.

Improved Efficiency, Reduced Lifetime Costs: e.g. for a 37kW load, operating 10 hours per day, 5 days per week, 50 weeks per year, improving the efficiency by just 1% will provide an energy saving > 900kWh per year.



Typical efficiency comparison for Optidrive Eco Pump vs other AC variable speed drives

■ Standard AC Variable Speed Drive
■ AC Variable Speed Drive + 4% Line Choke
■ Optidrive Eco Pump

OPTIFLOW™ Multi-pump Control

Embedded control technology for multi-pump systems

Flexible pump station control with no PLCs or pump control units

Setpoint Control

A standard
feature on
all drives

Pump Prime Mode



Pump Prime with Burst Pipe Detection

Pump prime mode allows starting of the pump in a safely controlled manner, to ensure consistent filling and pressurisation of pipe work and systems. Low pressure warnings are ignored during priming to allow the system to prime correctly, whilst a failsafe timeout prevents the pump from continuing to run in the event of a failure to prime. This helps to prevent the effects of water hammering (such as bursting water pipes) or damage to fountain / sprinkler heads.

The time limit, set for pump prime mode to complete, means that the pressure in the system must reach the minimum level within the set time. Failure of the system to pressurise would indicate a leak or burst pipe within the pump system and result in the Optidrive Eco Pump shutting down the pump. During normal operation the system pressure is still continuously monitored against the minimum level so that a burst pipe during normal operation will likewise result in the drive tripping 'low pressure' and shutting the pump down.

Independent pump
control system

Optiflow
Communications

← Feedback
signal

Total Control

A single 'Master' drive acts to control and monitor system operation. Control connections are made to this drive only, saving installation time and reducing costs.

Simple Connection

Additional drives connected on the system require a single RJ45 connection and basic commissioning, leading to time savings and simplified installation.

Flexible Solution

The system can operate with up to five pumps in any configuration, e.g. Jockey Pump / Duty / Assist / Standby. Duty pumps are automatically rotated, ensuring maximum service life and system efficiency.



Energy efficient pumping with **OPTIFLOW™**




See **OPTIFLOW™** in action

Scan to watch the video or visit
<http://youtu.be/9QQ89bQYdfs>

Avoid Pump Downtime

Blockage Detect/Clear

Optidrive Eco Pump can detect pump blockages and trigger a programmed cleaning cycle to automatically clear them, preventing downtime.



Dry Run Protection

Optidrive Eco Pump can evaluate a pump's speed/power and shut it off or warn when the pump starts to run dry, protecting it from heat/friction damage.

Motor Preheat Function

Optidrive Eco Pump features a motor preheat function to help ensure moisture is not permitted to collect on the motor in periods of inactivity and prior to motor start up. In addition, the motor preheat function can be used to keep condensation from developing on the motor as the motor cools down immediately following a stop. The feature is fully configurable, meaning the pump can be always available the instant it is required.

Pump Stir Cycle

Triggered by a settable period of inactivity, a configurable cleaning cycle can be run to clear sediment, ensuring the pump is ready to run when needed.

Summary

- All drives operate at variable speed for maximum energy efficiency.
- Operating time (Hours Run) is automatically balanced and duty pumps rotated
- Automatic system reconfiguration in the event of a pump fault (including the master pump).
- Continued system operation when drives are individually powered off (including the master drive).
- Communication and +24V control voltage shared between drives via a standard RJ45 patch lead.
- Independent maintenance indicators for each pump.
- Any pump can be switched to Hand operation a the touch of a button, and will automatically rejoin the network when switched back to Auto.
- For waste water applications each pump can be set for blockage/ragging detection and activate an automatic de-ragging/pump cleaning cycle.
- Optional mains isolator with lock-off for safe pump maintenance.
- Optiflow function configured through simple parameter set-up and intelligent drive self configuration.

Consistent Flow

The required pressure and flow levels are maintained regardless of how many pumps are required. When demand increases, additional pumps are automatically brought on stream to assist and are switched off again when not required.

Reduced Downtime

In the event of a fault, or if a pump needs to be isolated for maintenance, the system will automatically continue to operate with the remaining available pumps. The mains power can even be completely isolated from the Master drive without affecting operation of the Slave drives.

Drive Features

A compact and robust range of drives dedicated to pump control



Internal EMC Filter
Compliant with global EMC Standards

Time left to next service
20 hrs

Maintenance interval timer and service indication

Select Language
Español
Deutsch
▶ English

Multi Language OLED Display

HAND AUTO

Hand / Auto Keypad

16 17 18 19 10 11 12

Pluggable terminals

Integrated cable management

Long Life, Dual Ball Bearing Fans

Enclosure Options

IP66 with optional mains disconnect

OLED Display

Installed as standard on all IP55 & IP66 models


- Clear multi-line text display
- Operates -10 to 50°C
- Wide viewing angle, effective in dark and light conditions
- Customisable display
- Multi-language selection



Energy efficient pumping with **OPTIFLOW™**



Noise Reduction



Quiet Motor Operation

High switching frequency selection (up to 32kHz) ensures motor noise is minimised.

Quiet System Mechanics

Simple skip frequency selection avoids stresses and noise caused by mechanical resonance in pipework.

Quiet Drive Operation

Long Life Dual Ball Bearing Fans provide quiet operation in addition to extended fan life.

Noise Reduction through Speed Control


Optimising motor speed gives significant energy savings and reduces motor noise.

Reduced Harmonic Current Distortion

Optidrive Eco Pump uses innovative design to improve overall efficiency whilst minimising the harmonic distortion levels. All drives designed for 3 phase power supply operation¹ up to frame size 5 utilise film capacitor in the DC link, providing exceptionally low harmonic current distortion without compromising efficiency. Frame size 6 and above include DC chokes and traditional electrolytic capacitors.

Optidrive Eco Pump product range complies with the requirements of EN61000-3-12.

Typical iTHD values at full and part load




It can be clearly seen that the reduced DC link capacitance significantly reduces the total harmonic distortion at full load, and has a much greater benefit at part load compared to a conventional DC choke or swinging choke. This results in reduced overall input current and reduced transformer heating effect.

Optidrive Eco Pump delivers

- Improved Efficiency, Reduced Lifetime Costs: e.g. for a 37kW load, operating 10 hours per day, 5 days per week, 50 weeks per year, improving the efficiency by just 1% will provide an energy saving > 900kWh per year
- Improved True Power Factor – No additional charges etc.
- Lower Mains Supply Current

Power factor comparison




Optidrive Eco offers improved power factor over conventional VFDs under all loads.

¹ 200V and 400V

Options & Accessories

Peripherals to help integrate Optidrive Eco Pump with your pumping systems



Optistick



Rapid Commissioning Tool

Plug-in or wirelessly copy parameter sets between drives.

OPT-2-STICK-IN

Optipad



Remote Keypad & OLED Display

IP55 panel mount operator interface.

- Clear multi-line text display
- Multiple language select
- Customisable displays

OPT-2-OPPAD-IN


ASHRAE **BACnet**[®]
MS/TP
built-in as standard





Energy efficient pumping with **OPTIFLOW™**

OptiTools Studio



Powerful PC Software

Drive commissioning and parameter backup

- Real-time parameter editing
- Drive network communication
- Parameter upload, download and storage
- Simple PLC function programming
- Real-time scope function and data logging
- Real-time data monitoring

Compatible with:

- Windows XP
- Windows Vista
- Windows 7
- Windows 8
- Windows 8.1
- Windows 10

Fieldbus Interfaces



BACnet/IP
OPT-2-BNTIP-IN



PROFIBUS DP
OPT-2-PROFB-IN



DeviceNet
OPT-2-DEVNT-IN



EtherNet/IP
OPT-2-ETHNT-IN



Modbus TCP
OPT-2-MODIP-IN



PROFINET
OPT-2-PFNET-IN



EtherCAT
OPT-2-ETCAT-IN



Plug-in Options



Extended I/O
OPT-2-EXTIO-IN

- Additional 3 Digital Inputs
- Additional Relay Output

Cascade Control

OPT-2-CASCD-IN
Additional 3 Relay Outputs

Mains Isolator



Mains Isolator Option

Frame Sizes 2 & 3 can be factory ordered with a built in lockable isolator. An optional bolt on isolator is available for Frame Sizes 4 & 5.

Product Codes:

Frame Size 4 = OPT-2-ISOL4-IN
Frame Size 5 = OPT-2-ISOL5-IN

BACnet MS/TP & Modbus RTU on board as standard

	kW	HP	Amps	Size	Model Code	Product Family	Generation	Frame Size	Voltage Code	Output Rating	Supply Phases	EMC Filter	CE Marking	Enclosure Type	Display	PCB Coating
200–240V ± 10% 1 Phase Input	0.75	1	4.3	2	ODV - 3 - 2 2 0043 - 1 F 1							#	#	N		
	1.5	2	7	2	ODV - 3 - 2 2 0070 - 1 F 1							#	#	N		
	2.2	3	10.5	2	ODV - 3 - 2 2 0105 - 1 F 1							#	#	N		
200–240V ± 10% 3 Phase Input	0.75	1	4.3	2	ODV - 3 - 2 2 0043 - 3 F 1							#	#	N		
	1.5	2	7	2	ODV - 3 - 2 2 0070 - 3 F 1							#	#	N		
	2.2	3	10.5	2	ODV - 3 - 2 2 0105 - 3 F 1							#	#	N		
	4	5	18	3	ODV - 3 - 3 2 0180 - 3 F 1							#	#	N		
	5.5	7.5	24	3	ODV - 3 - 3 2 0240 - 3 F 1							#	#	N		
	7.5	10	30	4	ODV - 3 - 4 2 0300 - 3 F 1							#	T	N		
	11	15	46	4	ODV - 3 - 4 2 0460 - 3 F 1							#	T	N		
	15	20	61	5	ODV - 3 - 5 2 0610 - 3 F 1							#	T	N		
	18.5	25	72	5	ODV - 3 - 5 2 0720 - 3 F 1							#	T	N		
	22	30	90	5	ODV - 3 - 5 2 0900 - 3 F 1							#	T	N		
	30	40	110	6	ODV - 3 - 6 2 1100 - 3 F 1							N	T	N		
	37	50	150	6	ODV - 3 - 6 2 1500 - 3 F 1							N	T	N		
	45	60	180	6	ODV - 3 - 6 2 1800 - 3 F 1							N	T	N		
	55	75	202	7	ODV - 3 - 7 2 2020 - 3 F 1							N	T	N		
75	100	248	7	ODV - 3 - 7 2 2480 - 3 F 1							N	T	N			
380–480V ± 10% 3 Phase Input	0.75	1	2.2	2	ODV - 3 - 2 4 0022 - 3 F 1							#	#	N		
	1.5	2	4.1	2	ODV - 3 - 2 4 0041 - 3 F 1							#	#	N		
	2.2	3	5.8	2	ODV - 3 - 2 4 0058 - 3 F 1							#	#	N		
	4	5	9.5	2	ODV - 3 - 2 4 0095 - 3 F 1							#	#	N		
	5.5	7.5	14	3	ODV - 3 - 3 4 0140 - 3 F 1							#	#	N		
	7.5	10	18	3	ODV - 3 - 3 4 0180 - 3 F 1							#	#	N		
	11	15	24	3	ODV - 3 - 3 4 0240 - 3 F 1							#	#	N		
	15	20	30	4	ODV - 3 - 4 4 0300 - 3 F 1							#	T	N		
	18.5	25	39	4	ODV - 3 - 4 4 0390 - 3 F 1							#	T	N		
	22	30	46	4	ODV - 3 - 4 4 0460 - 3 F 1							#	T	N		
	30	40	61	5	ODV - 3 - 5 4 0610 - 3 F 1							#	T	N		
	37	50	72	5	ODV - 3 - 5 4 0720 - 3 F 1							#	T	N		
	45	60	90	5	ODV - 3 - 5 4 0900 - 3 F 1							#	T	N		
	55	75	110	6	ODV - 3 - 6 4 1100 - 3 F 1							N	T	N		
	75	100	150	6	ODV - 3 - 6 4 1500 - 3 F 1							N	T	N		
	90	150	180	6	ODV - 3 - 6 4 1800 - 3 F 1							N	T	N		
	110	175	202	7	ODV - 3 - 7 4 2020 - 3 F 1							N	T	N		
132	200	240	7	ODV - 3 - 7 4 2400 - 3 F 1							N	T	N			
160	250	302	7	ODV - 3 - 7 4 3020 - 3 F 1							N	T	N			
200	300	370	8	ODV - 3 - 8 4 3700 - 3 F 1							2	T	N			
250	350	450	8	ODV - 3 - 8 4 4500 - 3 F 1							2	T	N			
500–600V ± 10% 3 Phase Input	0.75	1	2.1	2	ODV - 3 - 2 6 0021 - 3 0 1							#	#	N		
	1.5	2	3.1	2	ODV - 3 - 2 6 0031 - 3 0 1							#	#	N		
	2.2	3	4.1	2	ODV - 3 - 2 6 0041 - 3 0 1							#	#	N		
	4	5	6.5	2	ODV - 3 - 2 6 0065 - 3 0 1							#	#	N		
	5.5	7.5	9	2	ODV - 3 - 2 6 0090 - 3 0 1							#	#	N		
	7.5	10	12	3	ODV - 3 - 3 6 0120 - 3 0 1							#	#	N		
	11	15	17	3	ODV - 3 - 3 6 0170 - 3 0 1							#	#	N		
	15	20	22	4	ODV - 3 - 4 6 0220 - 3 0 1							#	T	N		
	18.5	25	28	4	ODV - 3 - 4 6 0280 - 3 0 1							#	T	N		
	22	30	34	4	ODV - 3 - 4 6 0340 - 3 0 1							#	T	N		
	30	40	43	4	ODV - 3 - 4 6 0430 - 3 0 1							#	T	N		
	37	50	54	5	ODV - 3 - 5 6 0540 - 3 0 1							#	T	N		
	45	60	65	5	ODV - 3 - 5 6 0650 - 3 0 1							#	T	N		
	55	75	78	6	ODV - 3 - 6 6 0780 - 3 0 1							N	T	N		
75	100	105	6	ODV - 3 - 6 6 1050 - 3 0 1							N	T	N			
90	125	130	6	ODV - 3 - 6 6 1300 - 3 0 1							N	T	N			
110	150	150	6	ODV - 3 - 6 6 1500 - 3 0 1							N	T	N			

Enclosure & Display Types


Replace # in model code with colour-coded option

- 2-SN**  **IP20**
LED Display
- X-TN**  **IP66** Non-switched
OLED Display
- D-TN**  **IP66** Switched
OLED Display
- 2-TN**  **IP20**
OLED Display
- N-TN**  **IP55**
OLED Display
- N-TN**  **IP55**
OLED Display
- 2-TN**  **IP20**
OLED Display


Drive Specification

Input Ratings	Supply Voltage	200 – 240V ± 10% 380 – 480V ± 10% 500 – 600V ± 10%	I/O Specification	Power Supply	24 Volt DC, 100mA, Short Circuit Protected 10 Volt DC, 5mA for Potentiometer
	Supply Frequency	48 – 62Hz		Programmable Inputs	5 Total as standard (optional additional 3) 3 Digital (optional additional 3) 2 Analog / Digital selectable
Output Ratings	Displacement Power Factor	> 0.98	Digital Inputs	Opto - Isolated 8 – 30 Volt DC, internal or external supply Response time < 4ms	
	Phase Imbalance	3% Maximum allowed	Analog Inputs	Resolution: 12 bits Response time: < 4ms Accuracy: < 1% full scale Parameter adjustable scaling and offset	
	Inrush Current	< rated current	PTC Input	Motor PTC / Thermistor Input Trip Level : 3kΩ	
	Power Cycles	120 per hour maximum, evenly spaced	Programmable Outputs	2 Total 1 Analog / Digital 1 Relay	
	Output Power	230V 1Ph. Input: 0.75–2.2kW (1–3HP) 230V 3Ph. Input: 0.75–75kW (1–100HP) 400V 3Ph. Input: 0.75–250kW 460V 3Ph. Input: 1–350HP 575V 3Ph. Input: 0.75–110kW (1–150HP)	Relay Outputs	Maximum Voltage: 250 VAC, 30 VDC Switching Current Capacity: 5A	
Overload Capacity	110% for 60 seconds 165% for 4 seconds	Analog Outputs	0 to 10 Volts / 10 to 0 Volts 0 to 20mA / 20 to 0mA 4 to 20mA / 20 to 4mA		
Output Frequency	0 – 250Hz, 0.1Hz resolution	Application Features	PID Control	Internal PID Controller Multi-setpoint Select Standby / Sleep Mode Boost Function	
Typical Efficiency	> 98%		Fire Mode	Bidirectional Selectable Speed Setpoint (Fixed / PID / Analog / Fieldbus)	
Ambient Conditions	Temperature	Storage: –40 to 60°C Operating: –10 to 50°C	Load Monitoring	Over Torque Protection (Fan / Bump Blocked) Under Torque Protection (Broken Belt / Shaft) Pump Blockage Detection with Cleaning	
	Altitude	Up to 1000m ASL without derating Up to 2000m maximum UL approved Up to 4000m maximum (non UL)	Duty / Assist / Standby	Built-in Multi-Pump Support Automatic Changeover on Fault Automatic Changeover on Time Fully Redundant	
	Humidity	95% Max, non condensing	Pump Control Features	Pump Blockage Detection	Pump load monitoring with autotune function, user configurable
	Vibration	Conforms to EN61800-5-1 2007, IEC 60068-2-6		Pump Cleaning	Adjustable Bi-directional Pump Cleaning Cycle operation
Enclosure	Ingress Protection	IP20, IP55, IP66	Multi-Pump Control	Control of fixed speed assist pumps (with cascade control module) Control of Duty, Assist and Standby variable speed pumps via internal Master – Slave network	
	Programming	Keypad Built-in keypad as standard Optional remote mountable keypad	Pump Stir	Automatic pump stir to prevent sediment build-up	
Control Specification	Display	Built-in multi language OLED (IP55 & IP66) 7 Segment LED (IP20)	Maintenance & Diagnostics	Fault Memory	Last 4 Trips stored with time stamp
	PC	OptiTools Studio		Data Logging	Logging of data prior to trip for diagnostic purposes : Output Current Drive Temperature DC Bus Voltage
	Control Method	Eco Sensorless Vector Open Loop Permanent Magnet Vector Open Loop BLDC Vector Open Loop Synchronous Reluctance Vector	Maintenance Indicator	Maintenance Indicator with user adjustable maintenance interval Onboard service life monitoring	
	PWM Frequency	4 – 32kHz Effective	Monitoring	Hours Run Meter Resettable & Non-Resettable kWh meters Cooling Fan Run Time	
	Stopping Mode	Ramp to stop: User Adjustable 0.1–600 secs Coast to stop	Standards Compliance	Low Voltage Directive	2014/35/EU
Braking	AC Flux Braking	EMC Directive		2014/30/EU	
Fieldbus Connectivity	Skip Frequency	Single point, user adjustable	Additional Conformance	UL, cUL, EAC, RCM	
	Setpoint Control	Analog Signal 0 to 10 Volts / 10 to 0 Volts –10 Volts to +10 Volts 0 to 20mA / 20 to 0mA 4 to 20mA / 20 to 4mA	Harmonic Currents	IEC61000-3-12	
Built-in	Digital	Motorised Potentiometer (Keypad) Modbus RTU BACnet MS/TP	Environmental Conditions	Designed to meet IEC 60721-3-3, in operation: IP20 Drives: 3S2/3C2 IP55 & 66 Drives: 3S3/3C3	
	Optional	BACnet/IP Plug-in BACnet/IP interface Dual LAN ports Device Level Ring			
	Other	PROFIBUS DP (DPV1) PROFINET IO DeviceNet EtherNet/IP EtherCAT Modbus TCP			

Model Code Guide



Connection Diagram



NOT TO SCALE

Size	IP20					IP66			IP55			
	2	3	4	5	8	2	3	4	5	6	7	
mm Height	221	261	418	486	995	257	310	450	540	865	1280	
mm Width	110	131	160	222	482	188	211	171	235	330	330	
mm Depth	185	205	240	260	480	239	266	252	270	330	360	
kg Weight	1.8	3.5	8.1	17	128	4.8	7.7	11.5	23	55	89	

Optidrive Eco Pump

✓ Saving Energy / Reducing CO₂

With large scale increases in global energy costs and the introduction of taxes and legislation relating to the industrial production of CO₂ gases the need to reduce energy consumption and save money has never been greater. Optidrive Eco Pump can be used with environmental sensors to reduce pump speed in pumping applications without compromising the required output of the system.

✓ Easy Installation

Compact and modern design utilising the latest available technology have accumulated in a robust Eco Pump drive with small dimensions and innovative mounting and cabling features.

✓ Simple Set-up & Rapid Commissioning

Optidrive Eco Pump was developed from concept for ease of use. A handful of parameters configure the drive for basic pump applications. A short, concise product data means the drive is running in seconds. Advanced powerful functionality is equally easily accessible.

✓ Imaginative Enclosure Design

With a selection of IP55 and IP66 enclosures, Optidrive Eco Pump is well suited to harsh environments, or where cabinet and cabling costs need to be reduced.

✓ Advanced Pump Control Functions

The key pump control functionality required for your application is inbuilt into Optidrive Eco Pump and packaged to be both quick and simple to activate. Added to this is the drive's own PLC programming flexibility that makes drive functionality virtually limitless.

✓ Options for Flexibility

Optidrive Eco Pump combines both peripheral and factory built options to ensure you get the right drive, scaled to suit your application. With inbuilt BACnet and Modbus, and a host of communication options the Optidrive can integrate easily into your industrial network of choice.



UK Headquarters, Welshpool

Invertek Drives Ltd is dedicated to the design, manufacture and marketing of electronic variable speed drives. The state of the art UK headquarters houses specialist facilities for research & development, manufacturing and global marketing. The company pledges to implement and operate the ISO 14001 Environmental Management System to enhance environmental performance.

All company operations are accredited to the exacting customer focused ISO 9001:2008 quality standard. The company's products are sold globally in over 80 different countries. Invertek Drives' unique and innovative drives are designed for ease of use and meet with recognised international design standards.

Global Pump Solutions

Invertek Drives operate at the heart of pumping systems around the world



IRELAND
Maintaining pressure at pumping stations



HOLLAND
Hot water pumping across district network



ITALY
Cooling loop flow & temperature control



AUSTRALIA
Improved reliability & running costs



www.invertekdrives.com/pump-control

INVERTEK DRIVES LIMITED UK Headquarters

Offa's Dyke Business Park
Welshpool, Powys, UK
SY21 8JF

Tel: +44 (0)1938 556868
Fax: +44 (0)1938 556869
Email: sales@invertekdrives.com

