

# ODP-2-22220-1KF42-MN

Optidrive P2 VFD Datasheet

**2.2 kW, 10.5 A, 200-240 V, 1-3PH**  
IP20 Variable Frequency Drive with EMC  
Filter and TFT Display



### Input Ratings

Supply Voltage	200-240 V
Input Phases	1
Supply Current Continuous	19.5 A
Supply Fuse or MCB (Type B)	25 A

### Output Ratings

Motor Output Rating	2.2 kW (3 HP)
Output Voltage	0 – Supply Voltage
Output Current	10.5 A

### Cable Information

Max Supply Cable Size	8 mm <sup>2</sup> (0.01 sq in)
Max Motor Cable Size	8 mm <sup>2</sup> (0.01 sq in)
Max Motor Cable Length	100 m (328 ft)

### Factory Build Options

EMC Filter	Internal EMC
Brake Transistor	Internal
Enclosure	IP20
Display	TFT Display
PCB Coating	Standard


### Dimensions

Size	2
Height	221 mm (8.7 in)
Width	110 mm (4.33 in)
Depth	185 mm (7.28 in)
Weight	1.8 kg (3.97 lbs)
Fixings	4 x M4

### Packaged Dimensions

Height	265 mm (10.43 in)
Width	145 mm (5.71 in)
Depth	230 mm (9.06 in)
Weight	1.9 kg (4.19 lbs)



 **Buy this drive or get more information**  
Find your local sales partner on  
[invertekdrives.com](http://invertekdrives.com)

