

# ODP-2-54300-3KF42-MN

Optidrive P2 VFD Datasheet

**30 kW, 61 A, 380-480 V, 3PH**

IP20 Variable Frequency Drive with EMC Filter and TFT Display



## Input Ratings

Supply Voltage	380-480 V
Input Phases	3
Supply Current Continuous	63.8 A
Supply Fuse or MCB (Type B)	80 A

## Output Ratings

Motor Output Rating	30 kW (40 HP)
Output Voltage	0 – Supply Voltage
Output Current	61 A

## Cable Information

Max Supply Cable Size	35 mm <sup>2</sup> (0.05 sq in)
Max Motor Cable Size	35 mm <sup>2</sup> (0.05 sq in)
Max Motor Cable Length	100 m (328 ft)

## Factory Build Options

EMC Filter	Internal EMC
Brake Transistor	Internal
Enclosure	IP20
Display	TFT Display
PCB Coating	Standard

## Dimensions

Size	5
Height	486 mm (19.13 in)
Width	222 mm (8.74 in)
Depth	260 mm (10.24 in)
Weight	22.5 kg (49.6 lbs)
Fixings	N/A

## Packaged Dimensions

Height	356 mm (14.02 in)
Width	336 mm (13.23 in)
Depth	658 mm (25.91 in)
Weight	25 kg (55.12 lbs)



 **Buy this drive or get more information**  
Find your local sales partner on [invertekdrives.com](http://invertekdrives.com)

